


## Mod. 4209 B

### WATERPROOF CASE

Industrial waterproof case



METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L</b> LENGTH | 420 mm |
| <b>W</b> WIDTH  | 300 mm |
| <b>D</b> DEPTH  | 95 mm  |
| <b>LID</b>      | 35 mm  |
| <b>BASE</b>     | 60 mm  |


#### EXTERNAL DIMENSIONS

|                 |        |
|-----------------|--------|
| <b>L</b> LENGTH | 457 mm |
| <b>W</b> WIDTH  | 367 mm |
| <b>D</b> DEPTH  | 118 mm |

#### OTHER DATA

|                                |                     |
|--------------------------------|---------------------|
| <b>WEIGHT EMPTY</b>            | 2 Kg                |
| <b>WEIGHT WITH FOAM</b>        | 2.4 Kg              |
| <b>WEIGHT WITH CUSTOM FOAM</b> | Kg                  |
| <b>VOLUME</b>                  | 12 lt               |
| <b>BUOYANCY</b>                | 6.8 Kg/max          |
| <b>OPERATING TEMPERATURE</b>   | °C min -33 / max 90 |

IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

|                 |             |
|-----------------|-------------|
| <b>L</b> LENGTH | 16 9/16 in  |
| <b>W</b> WIDTH  | 11 13/16 in |
| <b>D</b> DEPTH  | 3 3/4 in    |
| <b>LID</b>      | 1 3/8 in    |
| <b>BASE</b>     | 2 3/8 in    |

#### EXTERNAL DIMENSIONS

|                 |            |
|-----------------|------------|
| <b>L</b> LENGTH | 18 in      |
| <b>W</b> WIDTH  | 14 7/16 in |
| <b>D</b> DEPTH  | 4 5/8 in   |

#### OTHER DATA

|                                |                        |
|--------------------------------|------------------------|
| <b>WEIGHT EMPTY</b>            | 4.85 lbs               |
| <b>WEIGHT WITH FOAM</b>        | 5.29 lbs               |
| <b>WEIGHT WITH CUSTOM FOAM</b> | lbs                    |
| <b>VOLUME</b>                  | 3.17 gal               |
| <b>BUOYANCY</b>                | 14.99 lbs/max          |
| <b>OPERATING TEMPERATURE</b>   | °F min -27.4 / max 194 |