


## Mod. 5326 B

### COPOLYMER POLYPROPYLENE WATERPROOF CASE

Transport cases resistant to chemicals, humidity and dust. Resistant to harshest temperatures (-33°C / +90°C). Custom foams available on demand. Self oiling free running wheels.



#### METRIC MM-KG-C°



#### INTERNAL DIMENSIONS

L LENGTH	538 mm
W WIDTH	405 mm
D DEPTH	250 mm
LID	60 mm
BASE	190 mm


#### EXTERNAL DIMENSIONS

L LENGTH	627 mm
W WIDTH	475 mm
D DEPTH	292 mm

#### OTHER DATA

WEIGHT EMPTY	10 Kg
WEIGHT WITH FOAM	11.25 Kg
WEIGHT WITH CUSTOM FOAM	Kg
VOLUME	53 lt
BUOYANCY	37.20 Kg/max
OPERATING TEMPERATURE	°C min -33 / max +90

#### IMPERIAL IN-LBS-F°



#### INTERNAL DIMENSIONS

L LENGTH	21 3/16 in
W WIDTH	15 15/16 in
D DEPTH	9 13/16 in
LID	2 3/8 in
BASE	7 1/2 in

#### EXTERNAL DIMENSIONS

L LENGTH	24 11/16 in
W WIDTH	18 11/16 in
D DEPTH	11 1/2 in

#### OTHER DATA

WEIGHT EMPTY	22.04 lbs
WEIGHT WITH FOAM	24.80 lbs
WEIGHT WITH CUSTOM FOAM	0 lbs
VOLUME	14 gal
BUOYANCY	82.01 lbs/max
OPERATING TEMPERATURE	°F min -27.4 / max +194